

CLAIMS

What is claimed is:

- 5 1. An on-chip inductor consisting of:

at least one dielectric layer;

at least one conductive winding on the at least one
10 dielectric layer; and

P-well having a major surface parallel to a major surface
of the dielectric layer.

- 15 2. The on-chip inductor of claim 1 further consists of:

a field oxide having a major surface that is juxtaposed to
the major surface of the P-well.

- 20 3. The on-chip inductor of claim 1 further consists of:

the at least one dielectric layer including one layer; and

the at least one conductive winding including a spiral
25 winding on the one layer.

4. The on-chip inductor of claim 1 further consists of:

the at least one dielectric layer includes a plurality of
30 layers; and

the at least conductive winding includes a plurality of windings on the plurality of layers.

5 5. The on-chip inductor of claim 1 further consists of:

the at least one dielectric layer includes a plurality of layers; and

10 the at least conductive winding includes a plurality of spiral windings on the plurality of layers.

6. The on-chip inductor of claim 1 further consists of:

15 a substrate having a major surface parallel to the major surface of the at least one dielectric layer.

7. The on-chip inductor of claim 1 further consists of:

20 a secondary winding magnetically coupled to the conductive winding.

8. The on-chip inductor of claim 1, wherein the at least one conductive winding further consists of:

25 center tap operably coupled to a reference potential to produce a differential inductor.

9. An on-chip inductor consisting of:

at least one dielectric layer;

5 at least one conductive winding on the at least one dielectric layer; and

field oxide layer having a major surface parallel to a major surface of the dielectric layer.

10

10. The on-chip inductor of claim 9 further consists of:

P-well having a major surface that is juxtaposed to the major surface of the field oxide layer.

15

11. The on-chip inductor of claim 9 further consists of:

a secondary winding magnetically coupled to the conductive winding.

20

12. The on-chip inductor of claim 9, wherein the at least one conductive winding further consists of:

center tap operably coupled to a reference potential to
25 produce a differential inductor.

13. An on-chip inductor consisting of:

at least one dielectric layer;

5 at least one conductive winding on the at least one dielectric layer; and

poly silicon layer having a major surface parallel to a major surface of the dielectric layer.

10

14. The on-chip inductor of claim 13 further consists of:

a secondary winding magnetically coupled to the conductive winding.

15

15. The on-chip inductor of claim 13, wherein the at least one conductive winding further consists of:

center tap operably coupled to a reference potential to produce a differential inductor.

20

16. A method for manufacturing an on-chip inductor consisting of:

creating at least one dielectric layer;

5

creating at least one conductive winding on the at least one dielectric layer; and

10

creating a P-well having a major surface parallel to a major surface of the dielectric layer.

17. The method of claim 16 further consists of:

15

creating a field oxide having a major surface that is juxtaposed to the major surface of the P-well.

18. The method of claim 16 further consists of:

20

creating the at least one dielectric layer to include one layer; and

creating the at least one conductive winding to include a spiral winding on the one layer.

25

19. The method of claim 16 further consists of:

creating the at least one dielectric layer to include a plurality of layers; and

30

creating the at least conductive winding to include a plurality of single windings on the plurality of layers.

20. The method of claim 16 further consists of:

creating the at least one dielectric layer to include a plurality of layers; and

5

creating the at least conductive winding to include a plurality of spiral windings one the plurality of layers.

21. The method of claim 16 further consists of:

10

creating a substrate having a major surface parallel to the major surface of the at least one dielectric layer.

22. The method of claim 16 further consists of:

15

creating a secondary winding magnetically coupled to the conductive winding.

23. The method of claim 16, wherein the at least one conductive winding further consists of:

20

creating a center tap operably coupled to a reference potential to produce a differential inductor.

24. A method for manufacturing an on-chip inductor consisting of:

creating at least one dielectric layer;

5

creating at least one conductive winding on the at least one dielectric layer; and

creating a field oxide layer having a major surface
10 parallel to a major surface of the dielectric layer.

25. The method of claim 24 further consists of:

15

creating a P-well having a major surface that is juxtaposed to the major surface of the field oxide layer.

26. The method of claim 24 further consists of:

20

creating a secondary winding magnetically coupled to the conductive winding.

27. The method of claim 24, wherein the at least one conductive winding further consists of:

25

creating a center tap operably coupled to a reference potential to produce a differential inductor.

28. A method for manufacturing an on-chip inductor consisting of:

creating at least one dielectric layer;

5

creating at least one conductive winding on the at least one dielectric layer; and

10

creating poly silicon layer having a major surface parallel to a major surface of the dielectric layer.

29. The method of claim 28 further consists of:

15

creating a secondary winding magnetically coupled to the conductive winding.

30. The method of claim 28, wherein the at least one conductive winding further consists of:

20

creating a center tap operably coupled to a reference potential to produce a differential inductor.